





Top Blend 85W140

Multi-viscosity Extreme-pressure Gear Oil

Fortified with multiple additives to meet the demands of new gearboxes and transmission systems



-  Multi-viscosity
-  Multi-purpose
-  Resists throw-off
-  Corrosion-inhibited

PROBLEM

High operating pressures cause oil breakdown

Need for high-quality gear oil

Tendency for oil to throw off gears at high rpm

Need for several different gear oils for different applications

SOLUTION

Top Blend 85W140 stands up to high pressures; lasts longer in use; extends equipment life.

Top Blend 85W140 has been boosted with multiple additives to greatly enhance the performance.

Top Blend 85W140 has remarkable adherence to metallic surfaces, which limits throw-off.

Top Blend 85W140 is multi-purpose and can be used effectively in a wide variety of applications.

Areas of Use Top Blend 85W140

- Manual transmissions
- Differentials
- Limited-slip differentials
- Axles
- Other types of industrial enclosed gearboxes requiring an ISO 460 gear oil



Top Blend 85W140



ADDITIVES

USER'S BENEFITS

Anti-oxidants	Longer service life
Corrosion inhibitors	Longer equipment life
Anti-wear	Longer equipment life
EP additives	Withstands high pressures
Friction modifiers	More-efficient operation

TECHNICAL DATA	
Weight	460
SAE Viscosity grade	85W140
Viscosity at 40°C cst	460
Viscosity at 100°C cst	32.4
Viscosity index	103
Flash point / C	231
Pour point / C	-22
FZG gear test (A/8.3/90) stage	12
Specific gravity	0.91
Viscosity at -12°C cP	40,000
Copper corrosion test	1b
API	GL5



REMARKS:

Not for use in automatic transmissions, farm or industrial tractors with combined transmissions, axle and hydraulic systems; or any other equipment where the manufacturer does not recommend this type of gear lubricant. Do not use with poly-glycol synthetic oils.

APPLICATION AREAS

- Construction
- Farms
- Factories
- Office buildings
- Warehouses
- Hospitals
- School districts
- Highway

* Consult the label for full instructions and precautions before using this product.

Kernite

A Division of NCH (Ireland) Ltd
 Unit 10, Brookville Business Park
 Ardee Road, Dundalk, County Louth
 Tel: 042 939 5500 Fax: 042 939 5501